



Night Sabre Discreet PoE LED Security Light

Crafted with the expertise of security installers and integrators in mind, our innovative security lights are powered from a PoE switch or injector through Cat5/6 cabling, spanning distances of up to 100 meters. Eliminating the need for an electrician, these lights can be easily installed by security integrators. The Normally Open alarm input allows further control from an external CCTV camera or alarm system with the NS-45P alarm input turning on the white light and the NS-45PA alarm input activating the strobing red and blue alarm LEDs. Additionally the NS-45PA has an alarm output that is triggered when the PIR detects movement at night

Integrating the NS-45PA with modern CCTV cameras allows the active deterrent feature to be triggered on advanced video analytic alarms such as tripwire or human detection. Connecting the active deterrent to an intruder alarm system creates a highly visual alarm signal.

- 1400 Lumens motion activated floodlight and 9m PIR
- PoE power so it can be run from an NVR or network switch up to 100m
- Discreet linear form factor for low profile installations
- Strobing red and blue LEDs on alarm input for active deterrent (NS-45PA)
- Alarm output from PIR for triggering other devices at night (NS-45PA)
- Alarm input turns on white LED floodlight (NS-45P)

	NS-45PA	NS-45P
Description	PoE connected security light with Active Deterrent	PoE connected security light
Power	PoE 802.3af	PoE 802.3af
Dimensions	485x35x35mm	480x30x30mm
Lumens	1400	1400
Detection	9m Digital PIR. 120°H x 90°V	9m Digital PIR
Adjustments	Dwell 10-400secs	Dwell 10-400secs
Alarm	N/O Alarm input trigger strobe N/O Alarm output from PIR at night	N/O Alarm input trigger LED
Weatherproof	IP-65	IP-65
Accessories	Mounting kit, weatherproof RJ-45 connector set	Mounting kit, weatherproof RJ-45 connector set
Features	Alarm input, alarm output, adjustable dwell	Alarm input for external control, adjustable dwell
Finishes	White - NS-45PAW Anthracite - NS-45PAB	White - NS-45PW Anthracite - NS-45PB





